

11/02/00

Jc920 U.S. PTO

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. P-1017

First Inventor or Application Identifier R.A. Mercuri et al

Title Flexible Graphite Sheet Having Increased

Express Mail Label No. EL063024312US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 20]
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 1]
4. Oath or Declaration [Total Pages]
- a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of
(when there is an assignee) Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
- * Small Entity
13. ☐ Statement(s) ☐ Statement filed in prior application,
(PTO/SB/09-12) Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

of prior application No: _____

Prior application information: Examiner _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

Name	James R. Cartiglia				
	Graftech Inc.				
Address	3102 West End Avenue, Suite 1100				
City	Nashville	State	Tennessee	Zip Code	37203
Country	USA	Telephone	615-760-7722	Fax	615-760-7785

Name (Print/Type)	James R. Cartiglia	Registration No. (Attorney/Agent)	30738
Signature		Date	11/2/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

<h1 style="margin: 0;">FEE TRANSMITTAL</h1> <h2 style="margin: 0;">for FY 2001</h2> <p style="margin: 5px 0 0 40px;">Patent fees are subject to annual revision.</p>		Complete if Known	
TOTAL AMOUNT OF PAYMENT (\$) 790.00		Application Number	
		Filing Date	
		First Named Inventor R.A. Mercuri et al	
		Examiner Name	
		Group Art Unit	
		Attorney Docket No. P-1017	

METHOD OF PAYMENT	FEE CALCULATION (continued)																																																																																																																																																																																								
<p>1. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to</p> <p>Deposit Account Number 50-1202</p> <p>Deposit Account Name UCAR Graph-Tech Inc.</p> <p><input type="checkbox"/> Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17</p> <p><input type="checkbox"/> Applicant claims small entity status See 37 CFR 1.27</p> <p>2. <input type="checkbox"/> Payment Enclosed:</p> <p><input type="checkbox"/> Check <input type="checkbox"/> Credit card <input type="checkbox"/> Money Order <input type="checkbox"/> Other</p>	<p>3. ADDITIONAL FEES</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Large Entity</th> <th colspan="2">Small Entity</th> <th rowspan="2">Fee Description</th> <th rowspan="2">Fee Paid</th> </tr> <tr> <th>Fee Code</th> <th>Fee (\$)</th> <th>Fee Code</th> <th>Fee (\$)</th> </tr> </thead> <tbody> <tr><td>105</td><td>130</td><td>205</td><td>65</td><td>Surcharge - late filing fee or oath</td><td></td></tr> <tr><td>127</td><td>50</td><td>227</td><td>25</td><td>Surcharge - late provisional filing fee or cover sheet</td><td></td></tr> <tr><td>139</td><td>130</td><td>139</td><td>130</td><td>Non-English specification</td><td></td></tr> <tr><td>147</td><td>2,520</td><td>147</td><td>2,520</td><td>For filing a request for <i>ex parte</i> reexamination</td><td></td></tr> <tr><td>112</td><td>920*</td><td>112</td><td>920*</td><td>Requesting publication of SIR prior to Examiner action</td><td></td></tr> <tr><td>113</td><td>1,840*</td><td>113</td><td>1,840*</td><td>Requesting publication of SIR after Examiner action</td><td></td></tr> <tr><td>115</td><td>110</td><td>215</td><td>55</td><td>Extension for reply within first month</td><td></td></tr> <tr><td>116</td><td>390</td><td>216</td><td>195</td><td>Extension for reply within second month</td><td></td></tr> <tr><td>117</td><td>890</td><td>217</td><td>445</td><td>Extension for reply within third month</td><td></td></tr> <tr><td>118</td><td>1,390</td><td>218</td><td>695</td><td>Extension for reply within fourth month</td><td></td></tr> <tr><td>128</td><td>1,890</td><td>228</td><td>945</td><td>Extension for reply within fifth month</td><td></td></tr> <tr><td>119</td><td>310</td><td>219</td><td>155</td><td>Notice of Appeal</td><td></td></tr> <tr><td>120</td><td>310</td><td>220</td><td>155</td><td>Filing a brief in support of an appeal</td><td></td></tr> <tr><td>121</td><td>270</td><td>221</td><td>135</td><td>Request for oral hearing</td><td></td></tr> <tr><td>138</td><td>1,510</td><td>138</td><td>1,510</td><td>Petition to institute a public use proceeding</td><td></td></tr> <tr><td>140</td><td>110</td><td>240</td><td>55</td><td>Petition to revive - unavoidable</td><td></td></tr> <tr><td>141</td><td>1,240</td><td>241</td><td>620</td><td>Petition to revive - unintentional</td><td></td></tr> <tr><td>142</td><td>1,240</td><td>242</td><td>620</td><td>Utility issue fee (or reissue)</td><td></td></tr> <tr><td>143</td><td>440</td><td>243</td><td>220</td><td>Design issue fee</td><td></td></tr> <tr><td>144</td><td>600</td><td>244</td><td>300</td><td>Plant issue fee</td><td></td></tr> <tr><td>122</td><td>130</td><td>122</td><td>130</td><td>Petitions to the Commissioner</td><td></td></tr> <tr><td>123</td><td>50</td><td>123</td><td>50</td><td>Petitions related to provisional applications</td><td></td></tr> <tr><td>126</td><td>240</td><td>126</td><td>240</td><td>Submission of Information Disclosure Stmt</td><td></td></tr> <tr><td>581</td><td>40</td><td>581</td><td>40</td><td>Recording each patent assignment per property (times number of properties)</td><td></td></tr> <tr><td>146</td><td>710</td><td>246</td><td>355</td><td>Filing a submission after final rejection (37 CFR § 1.129(a))</td><td></td></tr> <tr><td>149</td><td>710</td><td>249</td><td>355</td><td>For each additional invention to be examined (37 CFR § 1.129(b))</td><td></td></tr> <tr><td>179</td><td>710</td><td>279</td><td>355</td><td>Request for Continued Examination (RCE)</td><td></td></tr> <tr><td>169</td><td>900</td><td>169</td><td>900</td><td>Request for expedited examination of a design application</td><td></td></tr> <tr><td colspan="5">Other fee (specify) _____</td><td></td></tr> </tbody> </table>	Large Entity		Small Entity		Fee Description	Fee Paid	Fee Code	Fee (\$)	Fee Code	Fee (\$)	105	130	205	65	Surcharge - late filing fee or oath		127	50	227	25	Surcharge - late provisional filing fee or cover sheet		139	130	139	130	Non-English specification		147	2,520	147	2,520	For filing a request for <i>ex parte</i> reexamination		112	920*	112	920*	Requesting publication of SIR prior to Examiner action		113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action		115	110	215	55	Extension for reply within first month		116	390	216	195	Extension for reply within second month		117	890	217	445	Extension for reply within third month		118	1,390	218	695	Extension for reply within fourth month		128	1,890	228	945	Extension for reply within fifth month		119	310	219	155	Notice of Appeal		120	310	220	155	Filing a brief in support of an appeal		121	270	221	135	Request for oral hearing		138	1,510	138	1,510	Petition to institute a public use proceeding		140	110	240	55	Petition to revive - unavoidable		141	1,240	241	620	Petition to revive - unintentional		142	1,240	242	620	Utility issue fee (or reissue)		143	440	243	220	Design issue fee		144	600	244	300	Plant issue fee		122	130	122	130	Petitions to the Commissioner		123	50	123	50	Petitions related to provisional applications		126	240	126	240	Submission of Information Disclosure Stmt		581	40	581	40	Recording each patent assignment per property (times number of properties)		146	710	246	355	Filing a submission after final rejection (37 CFR § 1.129(a))		149	710	249	355	For each additional invention to be examined (37 CFR § 1.129(b))		179	710	279	355	Request for Continued Examination (RCE)		169	900	169	900	Request for expedited examination of a design application		Other fee (specify) _____					
Large Entity		Small Entity		Fee Description	Fee Paid																																																																																																																																																																																				
Fee Code	Fee (\$)	Fee Code	Fee (\$)																																																																																																																																																																																						
105	130	205	65	Surcharge - late filing fee or oath																																																																																																																																																																																					
127	50	227	25	Surcharge - late provisional filing fee or cover sheet																																																																																																																																																																																					
139	130	139	130	Non-English specification																																																																																																																																																																																					
147	2,520	147	2,520	For filing a request for <i>ex parte</i> reexamination																																																																																																																																																																																					
112	920*	112	920*	Requesting publication of SIR prior to Examiner action																																																																																																																																																																																					
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action																																																																																																																																																																																					
115	110	215	55	Extension for reply within first month																																																																																																																																																																																					
116	390	216	195	Extension for reply within second month																																																																																																																																																																																					
117	890	217	445	Extension for reply within third month																																																																																																																																																																																					
118	1,390	218	695	Extension for reply within fourth month																																																																																																																																																																																					
128	1,890	228	945	Extension for reply within fifth month																																																																																																																																																																																					
119	310	219	155	Notice of Appeal																																																																																																																																																																																					
120	310	220	155	Filing a brief in support of an appeal																																																																																																																																																																																					
121	270	221	135	Request for oral hearing																																																																																																																																																																																					
138	1,510	138	1,510	Petition to institute a public use proceeding																																																																																																																																																																																					
140	110	240	55	Petition to revive - unavoidable																																																																																																																																																																																					
141	1,240	241	620	Petition to revive - unintentional																																																																																																																																																																																					
142	1,240	242	620	Utility issue fee (or reissue)																																																																																																																																																																																					
143	440	243	220	Design issue fee																																																																																																																																																																																					
144	600	244	300	Plant issue fee																																																																																																																																																																																					
122	130	122	130	Petitions to the Commissioner																																																																																																																																																																																					
123	50	123	50	Petitions related to provisional applications																																																																																																																																																																																					
126	240	126	240	Submission of Information Disclosure Stmt																																																																																																																																																																																					
581	40	581	40	Recording each patent assignment per property (times number of properties)																																																																																																																																																																																					
146	710	246	355	Filing a submission after final rejection (37 CFR § 1.129(a))																																																																																																																																																																																					
149	710	249	355	For each additional invention to be examined (37 CFR § 1.129(b))																																																																																																																																																																																					
179	710	279	355	Request for Continued Examination (RCE)																																																																																																																																																																																					
169	900	169	900	Request for expedited examination of a design application																																																																																																																																																																																					
Other fee (specify) _____																																																																																																																																																																																									
<p>1. BASIC FILING FEE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Large Entity</th> <th colspan="2">Small Entity</th> <th rowspan="2">Fee Description</th> <th rowspan="2">Fee Paid</th> </tr> <tr> <th>Fee Code</th> <th>Fee (\$)</th> <th>Fee Code</th> <th>Fee (\$)</th> </tr> </thead> <tbody> <tr><td>101</td><td>710</td><td>201</td><td>355</td><td>Utility filing fee</td><td>710.</td></tr> <tr><td>106</td><td>320</td><td>206</td><td>160</td><td>Design filing fee</td><td></td></tr> <tr><td>107</td><td>490</td><td>207</td><td>245</td><td>Plant filing fee</td><td></td></tr> <tr><td>108</td><td>710</td><td>208</td><td>355</td><td>Reissue filing fee</td><td></td></tr> <tr><td>114</td><td>150</td><td>214</td><td>75</td><td>Provisional filing fee</td><td></td></tr> </tbody> </table> <p style="text-align: right;">SUBTOTAL (1) (\$) 710.00</p> <p>2. EXTRA CLAIM FEES</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Total Claims</th> <th>Extra Claims</th> <th>Fee from below</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr> <td>Independent Claims 20</td> <td>-20** = 0</td> <td>0</td> <td>0</td> </tr> <tr> <td>Multiple Dependent Claims 4</td> <td>-3** = 1</td> <td>80</td> <td>80</td> </tr> <tr> <td colspan="3"></td> <td></td> </tr> </tbody> </table> <p>Large Entity Small Entity</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Fee Code</th> <th>Fee (\$)</th> <th>Fee Code</th> <th>Fee (\$)</th> <th rowspan="2">Fee Description</th> </tr> </thead> <tbody> <tr><td>103</td><td>18</td><td>203</td><td>9</td><td>Claims in excess of 20</td></tr> <tr><td>102</td><td>80</td><td>202</td><td>40</td><td>Independent claims in excess of 3</td></tr> <tr><td>104</td><td>270</td><td>204</td><td>135</td><td>Multiple dependent claim, if not paid</td></tr> <tr><td>109</td><td>80</td><td>209</td><td>40</td><td>** Reissue independent claims over original patent</td></tr> <tr><td>110</td><td>18</td><td>210</td><td>9</td><td>** Reissue claims in excess of 20 and over original patent</td></tr> </tbody> </table> <p style="text-align: right;">SUBTOTAL (2) (\$) 790.00</p>	Large Entity		Small Entity		Fee Description	Fee Paid	Fee Code	Fee (\$)	Fee Code	Fee (\$)	101	710	201	355	Utility filing fee	710.	106	320	206	160	Design filing fee		107	490	207	245	Plant filing fee		108	710	208	355	Reissue filing fee		114	150	214	75	Provisional filing fee		Total Claims	Extra Claims	Fee from below	Fee Paid	Independent Claims 20	-20** = 0	0	0	Multiple Dependent Claims 4	-3** = 1	80	80					Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	103	18	203	9	Claims in excess of 20	102	80	202	40	Independent claims in excess of 3	104	270	204	135	Multiple dependent claim, if not paid	109	80	209	40	** Reissue independent claims over original patent	110	18	210	9	** Reissue claims in excess of 20 and over original patent	<p>SUBTOTAL (3) (\$) _____</p>																																																																																																		
Large Entity		Small Entity		Fee Description			Fee Paid																																																																																																																																																																																		
Fee Code	Fee (\$)	Fee Code	Fee (\$)																																																																																																																																																																																						
101	710	201	355	Utility filing fee	710.																																																																																																																																																																																				
106	320	206	160	Design filing fee																																																																																																																																																																																					
107	490	207	245	Plant filing fee																																																																																																																																																																																					
108	710	208	355	Reissue filing fee																																																																																																																																																																																					
114	150	214	75	Provisional filing fee																																																																																																																																																																																					
Total Claims	Extra Claims	Fee from below	Fee Paid																																																																																																																																																																																						
Independent Claims 20	-20** = 0	0	0																																																																																																																																																																																						
Multiple Dependent Claims 4	-3** = 1	80	80																																																																																																																																																																																						
Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description																																																																																																																																																																																					
103	18	203	9		Claims in excess of 20																																																																																																																																																																																				
102	80	202	40	Independent claims in excess of 3																																																																																																																																																																																					
104	270	204	135	Multiple dependent claim, if not paid																																																																																																																																																																																					
109	80	209	40	** Reissue independent claims over original patent																																																																																																																																																																																					
110	18	210	9	** Reissue claims in excess of 20 and over original patent																																																																																																																																																																																					

**or number previously paid, if greater; For Reissues, see above

*Reduced by Basic Filing Fee Paid

SUBMITTED BY		Complete (if applicable)	
Name (Print/Type)	James R. Cartiglia	Registration No (Attorney/Agent)	30738
Signature		Telephone	615-760-7722
		Date	11/2/00

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

New Patent Application

For

**FLEXIBLE GRAPHITE SHEET
HAVING INCREASED ISOTROPY**

Inventors:

Robert Angelo Mercuri
1007 East Decker Drive
Seven Hills, Ohio 44131

Jeffrey John Gough
7321 Pondside Point
Olmsted Township, Ohio 44138

Ronald Alfred Greinke
3931 Deer Lake Drive
Medina, Ohio 44256

Assignee:

Graftech Inc.
11709 Madison Avenue
Lakewood, Ohio 44107

Date of
Post NOV 2 2000 EXPRESS MAIL
Mailing Label No. E10630243/2 US
I hereby certify that this paper or fee is being
mailed with the United States Postal Service
First Class Mail Post Office to Addressee's service
under 37 CFR 1.10 on the date indicated above
and is addressed to the Commissioner of Patents
and Trademarks, Washington, D.C. 20231

LARRY CARAWELLA
(Typed or printed name of person
mailing paper or fee)

Larry Carawella
(Signature of person mailing paper
or fee)

5

Description

10

FLEXIBLE GRAPHITE SHEET HAVING INCREASED ISOTROPY

15 Field of the Invention

This invention relates to flexible graphite sheet that exhibits increased isotropy as compared with prior art flexible graphite sheet. More particularly, the present invention relates to a flexible graphite sheet having increased isotropy for forming gaskets as well as the components of an electrochemical fuel cell, including fluid flow field plates, seals and gas diffusion layers therefor.

20

Background of the Invention

Graphites are made up of layer planes of hexagonal arrays or networks of carbon atoms. These layer planes of hexagonally arranged carbon atoms are substantially flat and are oriented or ordered so as to be substantially parallel and equidistant to one another. The substantially flat, parallel equidistant sheets or layers of carbon atoms, usually referred to as basal planes, are linked or bonded together and groups thereof are arranged in crystallites. Highly ordered graphites consist of crystallites of considerable size: the crystallites being highly aligned or oriented with respect to each other and having well ordered carbon layers. In other words, highly ordered graphites have a high degree of preferred crystallite orientation. It should be noted that graphites exhibit anisotropy because of their inherent structure and thus exhibit or possess many properties that are highly directional, especially thermal and electrical conductivity and fluid diffusion. Briefly, graphites may be characterized as laminated structures of carbon, that is, structures consisting of superposed layers or laminae of carbon atoms joined together by weak van der Waals forces. In considering the graphite structure, two axes or directions are usually

25

30

noted, to wit, the "c" axis or direction and the "a" axes or directions. For simplicity, the "c" axis or direction may be considered as the direction perpendicular to the carbon layers. The "a" axes or directions may be considered as the directions parallel to the carbon layers or the directions perpendicular to the "c" direction. The natural graphites suitable for manufacturing flexible

5 graphite possess a very high degree of orientation.

As noted above, the bonding forces holding the parallel layers of carbon atoms together are only weak van der Waals forces. Graphites can be treated so that the spacing between the superposed carbon layers or laminae can be appreciably opened up so as to provide a marked
10 expansion in the direction perpendicular to the layers, that is, in the "c" direction and thus form an expanded or intumesced graphite structure in which the laminar character of the carbon layers is substantially retained.

Natural graphite flake which has been greatly expanded and more particularly expanded
15 so as to have a final thickness or "c" direction dimension which is at least about 80 or more times the original "c" direction dimension can be formed without the use of a binder into cohesive or integrated flexible graphite sheets of expanded graphite, e.g. webs, papers, strips, tapes, or the like. The formation of graphite particles which have been expanded to have a final thickness or "c" dimension which is at least about 80 times the original "c" direction dimension into
20 integrated flexible sheets by compression, without the use of any binding material is believed to be possible due to the excellent mechanical interlocking, or cohesion which is achieved between the voluminosely expanded graphite particles.

In addition to flexibility, the sheet material, as noted above, has also been found to
25 possess a high degree of anisotropy with respect to thermal and electrical conductivity and fluid diffusion, comparable to the natural graphite starting material due to orientation of the expanded graphite particles substantially parallel to the opposed faces of the sheet resulting from very high compression, e.g. roll pressing. Sheet material thus produced has excellent flexibility, good strength and a very high degree of orientation.

30

Briefly, the process of producing flexible, binderless anisotropic graphite sheet material, such as web, paper, strip, tape, foil, mat, or the like, comprises compressing or compacting under a predetermined load and in the absence of a binder, expanded graphite particles which have a “c” direction dimension which is at least about 80 times that of the original particles so as to form a substantially flat, flexible, integrated graphite sheet. The expanded graphite particles, which generally are worm-like or vermiform in appearance, once compressed, will maintain the compression set and alignment with the opposed major surfaces of the sheet. The density and thickness of the sheet material can be varied by controlling the degree of compression. The density of the sheet material can be within the range of from about 0.08 grams per cubic centimeters (g/cc) to about 2.0 g/cc. The flexible graphite sheet material exhibits an appreciable degree of anisotropy due to the alignment of graphite particles parallel to the major opposed, parallel surfaces of the sheet, with the degree of anisotropy increasing upon roll pressing of the sheet material to increased density. In roll pressed anisotropic sheet material, the thickness, *i.e.* the direction perpendicular to the opposed, parallel sheet surfaces comprises the “c” direction and the directions ranging along the length and width, *i.e.* along or parallel to the opposed, major surfaces comprises the “a” directions and the thermal, electrical and fluid diffusion properties of the sheet are very different, by orders of magnitude, for the “c” and “a” directions.

This very considerable difference in properties, known as anisotropy, which is directionally dependent, can be disadvantageous in some applications. For example, in gasket applications where flexible graphite sheet is used as the gasket material and in use is held tightly between metal surfaces, the diffusion of fluid, *e.g.* gases or liquids, occurs more readily parallel to and between the major surfaces of the flexible graphite sheet. It would, in most instances, provide for greater gasket performance, if the resistance to fluid flow parallel to the major surfaces of the graphite sheet (“a” direction) were increased, even at the expense of reduced resistance to fluid diffusion flow transverse to the major faces of the graphite sheet (“c” direction). With respect to electrical properties, the resistivity of anisotropic flexible graphite sheet is high in the direction transverse to the major surfaces (“c” direction) of the flexible graphite sheet, and very substantially less in the direction parallel to and between the major faces of the flexible graphite sheet (“a” direction). In applications such as fluid flow field plates, seals

and gas diffusion layers for fuel cells, it would be of advantage if the electrical resistance transverse to the major surfaces of the flexible graphite sheet ("c" direction) were decreased, even at the expense of an increase in electrical resistivity in the direction parallel to the major faces of the flexible graphite sheet ("a" direction).

5

With respect to thermal properties, the thermal conductivity of a flexible graphite sheet in a direction parallel to the upper and lower surfaces of the flexible graphite sheet is relatively high, while it is relatively very low in the "c" direction transverse to the upper and lower surfaces.

10

The foregoing situations are accommodated by the present invention.

Summary of the Invention

A method for making flexible graphite sheet, which includes treating graphite flake sized such that no more than about 30% by weight does not pass through an 80 mesh screen (referred to as +80 mesh) (unless otherwise indicated, all references to mesh sizes herein are to U.S. standard screens) with an intercalating solution to obtain heat expandable, intercalated graphite flake; exposing the graphite flake to an elevated temperature to exfoliate the flake into expanded particles of graphite; and passing the expanded particles of graphite through pressure rolls to form a compressed sheet formed of said blended mixture, the compressed sheet having opposed major surfaces. In other words, the graphite flake employed is sized such that at least about 70% by weight passes through an 80 mesh screen. The graphite flake most useful in the invention is sized such that at least about 50% by weight passes through an 80 mesh screen but not a 140 mesh screen (referred to as 80 x 140 mesh) and has a moisture content of no greater than about 1.0%.

25

In a preferred embodiment of the invention, transverse fluid channels are formed in the compressed sheet by mechanically impacting a surface of the sheet to displace graphite within the sheet at a plurality of predetermined locations, and at least one groove is formed in at least one of the surfaces of the sheet by mechanically impacting an opposed surface of the sheet.

30

The invention also comprises a flexible graphite sheet made in accordance with the inventive process, itself and as a sealing gasket or an electrode component of a membrane electrode assembly comprising a pair of electrodes and an ion exchange membrane positioned
5 between the electrodes.

Brief Description of the Drawings

10 FIG. 1 is a plan view of a transversely permeable sheet of flexible graphite having transverse channels in accordance with the present invention;

FIG. 1(A) shows a flat-ended protrusion element used in making the channels in the sheet of Figure 1;

15 FIG. 2 is a side elevation view in section of the sheet of Figure 1;

FIGS. 2(A), (B), (C) show various suitable flat-ended configurations for transverse channels in accordance with the present invention;

20 FIGS. 3, 3(A) shows a mechanism for making the article of Figure 1;

FIG. 4 is a scanning view electron microscope (SEM) at an original magnification of 50X showing natural graphite flake sized in the range of 80 x 140 mesh.

25 FIG. 5 is a sketch of an enlarged elevation view of an article formed of flexible graphite sheet having transverse channels for use with the present invention;

FIG. 6 is a top plan view of an article formed of the sheet material of Figure 1 having a
30 continuous open top groove formed in its upper surface in accordance with the present invention;

FIG. 6(A) is a sectional side elevation view of the material of the article of Figure 6; and

FIGS. 7, 8 and 8(A) show a fluid permeable electrode assembly which includes a

transversely permeable article in accordance with the present invention.

Detailed Description of the Invention

Graphite is a crystalline form of carbon comprising atoms bonded in flat layered planes with weaker bonds between the planes. By treating particles of graphite with an intercalant of, *e.g.*, a solution of sulfuric and nitric acid, the crystal structure of the graphite reacts to form a compound of graphite and the intercalant. Grinding, milling and other mechanical treatment of graphite can change the crystal orientation of graphite and the effectiveness of the intercalant. The graphite flake used in the present invention is sized such that no more than about 30% by weight of the flake is +80 mesh (U.S. standard screen). That is, no more than about 30% of the flake does not pass through an 80 mesh screen; put the other way, at least about 70% by weight of the flake passes through an 80 mesh screen. Most advantageously, graphite flake is sized at least about 50% by weight 80 x 140 mesh, U.S. standard screen (that is, at least about 50% of the flake passes through an 80 mesh screen but not a 140 mesh screen) and has a moisture content of no greater than about 1.0%.

The treated intercalated particles of graphite are known as particles of “expandable graphite.” Upon exposure to high temperature, the particles of intercalated graphite undergo intumescence and expand (or exfoliate) in dimension as much as about 80 or more times its original volume in an accordion-like fashion in the c-direction, *i.e.* in the direction perpendicular to the crystalline planes of the graphite. The exfoliated graphite particles are vermiform in appearance, and are therefore commonly referred to as worms.

Graphite starting materials suitable for use in the present invention include highly graphitic carbonaceous materials capable of reversibly intercalating alkali metals and then expanding when exposed to heat. These highly graphitic carbonaceous materials have a degree

of graphitization above about 0.80 and most preferably about 1.0. As used in this disclosure, the term “degree of graphitization” refers to the value g according to the formula:

$$g = \frac{3.45 - d(002)}{0.095}$$

where $d(002)$ is the spacing between the graphitic layers of the carbons in the crystal structure measured in Angstrom units. The spacing d between graphite layers is measured by standard X-ray diffraction techniques. The positions of diffraction peaks corresponding to the (002), (004) and (006) Miller Indices are measured, and standard least-squares techniques are employed to derive spacing which minimizes the total error for all of these peaks. Examples of highly graphitic carbonaceous materials include synthetic graphites and natural graphites from various sources, as well as other carbonaceous materials such as carbons prepared by chemical vapor deposition or pyrolysis of hydrocarbons and the like. Natural graphite is most preferred.

A common method for making expandable graphite particles is described by Shane *et al.* in U.S. Patent No. 3,404,061, the disclosure of which is incorporated herein by reference. In the typical practice of this method, natural graphite flakes are intercalated by dispersing the flakes in a solution containing an oxidizing agent, *e.g.*, a mixture of nitric and sulfuric acid. The intercalation solution contains oxidizing and other intercalating agents known in the art. Examples include those containing oxidizing agents and oxidizing mixtures, such as solutions containing nitric acid, potassium chlorate, chromic acid, potassium permanganate, potassium chromate, potassium dichromate, perchloric acid, and the like, or mixtures, such as for example, concentrated nitric acid and chlorate, chromic acid and phosphoric acid, sulfuric acid and nitric acid, or mixtures of a strong organic acid, *e.g.* trifluoroacetic acid, and a strong oxidizing agent soluble in the organic acid. Alternatively, an electric potential can be used to bring about oxidation of the graphite. Chemical species that can be introduced into the graphite crystal using electrolytic oxidation include sulfuric acid as well as other acids.

A preferred intercalating agent is a solution of a mixture of sulfuric acid, or sulfuric acid and phosphoric acid, and an oxidizing agent, *i.e.* nitric acid, perchloric acid, chromic acid, potassium permanganate, hydrogen peroxide, iodic or periodic acids, or the like. Although less preferred, the intercalation solutions may contain metal halides such as ferric chloride, and ferric

chloride mixed with sulfuric acid, or a halide, such as bromine as a solution of bromine and sulfuric acid or bromine in an organic solvent. Alternatively, an electric potential can be used to bring about oxidation of the graphite. Chemical species that can be introduced into the graphite crystal using electrolytic oxidation include sulfuric acid as well as other acids.

5

The quantity of intercalation solution may range from about 20 to 150 parts of solution by weight per 100 parts by weight of graphite flakes (pph) and more typically about 50 to 120 pph. In a preferred embodiment of the invention, after the flakes are intercalated excess solution is drained from the flakes and after washing with water, the intercalated graphite flakes are dried and are expandable upon exposure to high temperature. In an alternative embodiment, the quantity of the intercalation solution may be limited to between about 10 to 50 pph which permits the washing step to be eliminated as taught and described in U.S. Pat. No. 4,895,713, the disclosure of which is also herein incorporated by reference.

Advantageously, the particles of graphite flake treated with intercalant can be contacted *e.g.* by blending or mixing, with an organic reducing agent selected from alcohols, sugars, aldehydes and esters which are reactive with the surface film of oxidizing intercalating solution at temperatures in the range of 5°C and 125°C. Suitable specific organic agents include hexadecanol, octadecanol, 1-octanol, 2-octanol, decylalcohol, 1, 10 decanediol, decylaldehyde, 1-propanol, 1,3 propanediol, ethyleneglycol, polypropylene glycol, dextrose, fructose, lactose, sucrose, potato starch, ethylene glycol monostearate, diethylene glycol dibenzoate, propylene glycol monostearate, glycerol monostearate, dimethyl oxylate, diethyl oxylate, methyl formate, ethyl formate, ascorbic acid and lignin-derived compounds, such as sodium lignosulfate. The amount of organic reducing agent is suitably from about 0.5 to 4% by weight of the particles of graphite flake.

The use of an expansion aid applied prior to, during, or even after intercalation can also provide improvement, especially in terms of reduced exfoliation temperature, and/or increased expanded volume (also referred to as "worm volume") or pressure. An expansion aid in this context is preferably an organic material sufficiently soluble in the intercalant to achieve an

improvement in expansion characteristics. More narrowly, organic materials of this type that contain carbon, hydrogen and oxygen, preferably exclusively, may be employed. Carboxylic acids have been found to be especially effective. A suitable carboxylic acid as the expansion aid can be selected from aromatic, aliphatic or cycloaliphatic, straight chain or branched chain, saturated and unsaturated monocarboxylic acids, dicarboxylic acids and polycarboxylic acids which have at least 1 carbon atom, and preferably up to about 10 carbon atoms, which is soluble in the aqueous intercalant solution employed according to the invention in amounts effective to provide a measurable improvement of one or more aspects of exfoliation. Suitable water-miscible organic solvents can be employed to improve solubility of an organic expansion aid in the intercalant solution.

Representative examples of saturated aliphatic carboxylic acids are acids such as those of the formula $H(CH_2)_nCOOH$ wherein n is a number of from 0 to about 5, including formic, acetic, propionic, butyric, pentanoic, hexanoic, and the like. In place of the carboxylic acids, the anhydrides or reactive carboxylic acid derivatives such as alkyl esters can also be employed. Representative of alkyl esters are methyl formate and ethyl formate. Sulfuric acid, nitric acid and other known aqueous intercalants have the ability to decompose formic acid, ultimately to water and carbon dioxide. Because of this, formic acid and other sensitive expansion aids are advantageously contacted with the graphite flake prior to immersion of the flake in the intercalant.

Representative of dicarboxylic acids are aliphatic dicarboxylic acids having 2-12 carbon atoms, in particular oxalic acid, fumaric acid, malonic acid, maleic acid, succinic acid, glutaric acid, adipic acid, 1,5-pentanedicarboxylic acid, 1,6-hexanedicarboxylic acid, 1,10-decanedicarboxylic acid, cyclohexane-1,4-dicarboxylic acid and aromatic dicarboxylic acids such as phthalic acid or terephthalic acid. Representative of alkyl esters are dimethyl oxylate and diethyl oxylate. Representative of cycloaliphatic acids is cyclohexane carboxylic acid and of aromatic carboxylic acids are benzoic acid, naphthoic acid, anthranilic acid, p-aminobenzoic acid, salicylic acid, o-, m- and p-tolyl acids, methoxy and ethoxybenzoic acids, acetoacetamidobenzoic acids and, acetamidobenzoic acids, phenylacetic acid and naphthoic

acids. Representative of hydroxy aromatic acids are hydroxybenzoic acid, 3-hydroxy-1-naphthoic acid, 3-hydroxy-2-naphthoic acid, 4-hydroxy-2-naphthoic acid, 5-hydroxy-1-naphthoic acid, 5-hydroxy-2-naphthoic acid, 6-hydroxy-2-naphthoic acid and 7-hydroxy-2-naphthoic acid.

Prominent among the polycarboxylic acids is citric acid.

5

The intercalant solution will preferably contain an amount of expansion aid of from about 1 to 10%, the amount being effective to enhance exfoliation. In the embodiment wherein the expansion aid is contacted with the graphite flake prior to or after immersing of the flakes in the intercalant, the expansion aid can be admixed with the graphite by suitable means, such as a V-blender, typically in an amount of from about 0.2% to about 10% by weight of the graphite flake.

10

After intercalating the graphite flake with an intercalating solution, preferably containing an expansion aid, and following the blending of the intercalant coated intercalated graphite flake with the organic reducing agent, the blend is typically exposed to temperatures in the range of about 5° to 125°C to promote reaction of the reducing agent and intercalant coating. The heating period is up to about 20 hours, with shorter heating periods, *e.g.*, at least about 10 minutes, for higher temperatures in the above-noted range. Times of one half hour or less, *e.g.*, on the order of 10 to 25 minutes, can be employed at the higher temperatures.

15

The thus treated particles of graphite are hereafter referred to as “particles of intercalated graphite.” Upon exposure to high temperature, of up to at least about 700°C, and preferably 700°C to 1000°C or higher for a few seconds the particles of intercalated graphite expand in dimension as much as about 80 to 1000 or more times their original volume in an accordion-like fashion in the *c*-direction, *i.e.*, in the direction perpendicular to the crystalline planes of the graphite. In a preferred embodiment, the intercalated graphite flakes are exposed to this high temperature by exposing them to an open flame.

20

25

Flexible graphite sheet and foil are coherent, with good handling strength, and are suitably compressed, such as by roll-pressing, to a thickness preferably between about 0.075 and about 3.75 millimeters (mm) and a density that is advantageously between about 0.1 and about

30

1.5 g/cc. From about 1.5-30% by weight of ceramic additives, can be blended with the intercalated graphite flakes as described in U.S. Patent 5,902,762 (which is incorporated herein by reference) to provide enhanced resin impregnation in the final flexible graphite product. The additives include ceramic fiber particles having a length of 0.15 to 1.5 mm. The width of the particles is suitably from 0.04 to 0.004 mm. The ceramic fiber particles are non-reactive and non-adhering to graphite and are stable at temperatures up to about 1100°C, preferably up to about 1375°C. Suitable ceramic fiber particles are formed of macerated quartz glass fibers, carbon and graphite fibers, zirconia, boron nitride, silicon carbide and magnesia fibers, naturally occurring mineral fibers such as calcium metasilicate fibers, calcium aluminum silicate fibers, aluminum oxide fibers and the like.

Optionally, depending on the nature of the end use of the flexible graphite sheet, phosphorus is added to the intercalated unexfoliated graphite flakes of the batch by admixing with the flakes a phosphorus compound such as monoammonium phosphate in the form of a solid or solution. The phosphorus additive can be phosphoric acid (hypo-meta-ortho-pyro) acid salts for example ammonium, alumesium, alkaline metal, and alkaline earth metal salts and can be added in solid, or as a solution, to the intercalated graphite prior to drying. The amount of phosphorus added, as phosphorus, is from 0.2 to 0.6 percent by weight (2000 to 6000 ppm) of the unexfoliated intercalated graphite flakes. The use of a phosphorus addition to the unexfoliated, intercalated graphite particles leads to increased resistance to oxidation and corrosion of the flexible graphite sheet when used in automotive gasket applications and the like.

Once the expanded graphite particles are compressed into the form of a sheet having opposed first and second major surfaces, transverse fluid channels passing through the sheet between the first and second surfaces are preferably formed, most advantageously with at least one of the surfaces having an open top groove interconnecting with a plurality of the transverse fluid channels. The transverse fluid channels passing through the sheet between the opposed first and second surfaces can be formed by mechanically impacting a surface of the sheet to displace graphite within the sheet at a plurality of predetermined locations to provide the channels with openings at the first and second opposed surfaces. In a particular embodiment, the transverse

channel openings at one of the parallel opposed surfaces are smaller than their respective openings at the other opposed surface. Thus, pressurized fluid in contact with the opposed surface having the smaller channel openings enters the respective channels at an initial velocity which is greater than the velocity of the fluid exiting the respective channels, *i.e.*, the gas exit velocity is slowed. The sheet is preferably further mechanically deformed at one of its opposed surfaces, *e.g.* by engraving, to provide in the surface of the article an open top groove which interconnects with a plurality of the transverse fluid channels.

Detailed Description of the Preferred Embodiment

With reference to Figure 1, a compressed mass of expanded graphite particles, in the form of a flexible graphite sheet, is shown at 10. As noted above, the graphite flake used in to produce the expanded graphite particles is sized such that no more than about 30% by weight of the flake is +80 mesh (U.S. standard screen). Most preferably, graphite flake is sized at least about 50% by weight 80 x 140 mesh, U.S. standard screen and has a moisture content of no greater than about 1.0%. The flexible graphite sheet 10 is provided with channels 20, which are preferably smooth-sided as indicated at 67 in Figure 5, and which pass between the opposed surfaces 30, 40 of flexible graphite sheet 10, and are separated by walls 3 of compressed expandable graphite. The channels 20 preferably have openings 50 on one of the opposed surfaces 30 which are larger than the openings 60 in the other opposed surface 40. The channels 20 can have different configurations as shown at 20' - 20''' in Figures 2(A), 2(B), 2(C) which are formed using flat-ended protrusion elements of different shapes as shown at 75, 175, 275, 375 in Figures 1(A) and 2(A), 2(B), 2(C), suitably formed of metal, *e.g.* steel and integral with and extending from the pressing roller 70 of the impacting device shown in Figure 3. The smooth flat-ends of the protrusion elements, shown at 77, 177, 277, 377, and the smooth bearing surface 73, of roller 70, and the smooth bearing surface 78 of roller 72 (or alternatively flat metal plate 79), ensure deformation and complete displacement of graphite within the flexible graphite sheet, *i.e.* there are no rough or ragged edges or debris resulting from the channel-forming impact. Preferred protrusion elements have decreasing cross-section in the direction away from the pressing roller 70 to provide larger channel openings on the side of the sheet that is initially impacted. The

development of smooth, unobstructed surfaces 63 surrounding channel openings 60, enables the free flow of fluid into and through smooth-sided (at 67) channels 20.

In a preferred embodiment, openings on one of the opposed surfaces are larger than the channel openings in the other opposed surface, *e.g.* from 1 to 200 times greater in area, and result from the use of protrusion elements having converging sides such as shown at 76, 276, 376. The channels 20 are formed in the flexible graphite sheet 10 at a plurality of pre-determined locations by mechanical impact at the predetermined locations in sheet 10 using a mechanism such as shown in Figure 3 comprising a pair of steel rollers 70, 72 with one of the rollers having truncated, *i.e.* flat-ended, prism-shaped protrusions 75 which impact surface 30 of flexible graphite sheet 10 to displace graphite and penetrate sheet 10 to form open channels 20. In practice, both rollers 70, 72 can be provided with “out-of-register” protrusions, and a flat metal plate indicated at 79, can be used in place of smooth-surfaced roller 72.

This orientation of the expanded graphite particles 80 results in anisotropic properties in flexible graphite sheets; *i.e.* the electrical conductivity and thermal conductivity of the sheet being substantially lower in the direction transverse to opposed surfaces 130, 140 (“c” direction) than in the direction (“a” direction) parallel to opposed surfaces 130, 140. In the course of impacting flexible graphite sheet 10 to form channels 20, as illustrated in Figure 3, graphite is displaced within flexible graphite sheet 10 by flat-ended (at 77) protrusions 75 to push aside graphite as it travels to and bears against smooth surface 73 of roller 70 to disrupt and deform the parallel orientation of expanded graphite particles 80 as shown at 800 in Figure 5. This region of 800, adjacent channels 20, shows disruption of the parallel orientation into an oblique, non-parallel orientation is optically observable at magnifications of 100X and higher. In effect the displaced graphite is being “die-molded” by the sides 76 of adjacent protrusions 75 and the smooth surface 73 of roller 70 as illustrated in Figure 5. This reduces the anisotropy in flexible graphite sheet 10 and thus increases the electrical and thermal conductivity of sheet 10 in the direction transverse to the opposed surfaces 30, 40. A similar effect is achieved with frusto-conical and parallel-sided peg-shaped flat-ended protrusions 275 and 175.

In the practice of the present invention, with reference to Figures 6 and 6(A), a gas permeable flexible graphite sheet 10, as shown in Figure 1, is provided, at one of its surfaces 30 with a continuous, open groove 300, fluid inlet 303 and fluid outlet 305 to constitute a gas diffusing electrode 610. The groove 300 of the present invention is suitably formed by pressing a hard metal die onto the inventive flexible graphite sheet material, such as material of the type shown in Figure 2, *i.e.*, flexible graphite sheet having transverse channels 20 passing therethrough from surface 30 to surface 40. The die forms a continuous open groove 300 in the surface contacted by the die. For a sheet of flexible graphite 0.15 mm to 0.32 mm thick, open groove 300 can be, for instance, 0.076 mm to 0.16 mm deep and 0.5 mm to 0.6.35 mm wide separated by lands 400 that are 0.25 mm to 1.6 mm thick.

The perforated gas permeable flexible graphite sheet 10 of Figure 1 can be used as an electrode in an electrochemical fuel cell 500 shown schematically in Figures 7, 8 and 8(A).

Figure 7, Figure 8 and Figure 8(A) show, schematically, the basic elements of an electrochemical Fuel Cell, more complete details of which are disclosed in U.S. Patents 4,988,583 and 5,300,370 and PCT WO 95/16287 (15 June 1995) and each of which is incorporated herein by reference.

With reference to Figure 7, Figure 8 and Figure 8(A), the Fuel Cell indicated generally at 500, comprises electrolyte in the form of a plastic e.g. a solid polymer ion exchange membrane 550; perforated flexible graphite sheet electrodes 10 in accordance with the present invention; and flow field plates 1000, 1100 which respectively abut electrodes 10. Pressurized fuel is circulated through grooves 1400 of fuel flow field plate 1100 and pressurized oxidant is circulated through grooves 1200. In operation, the fuel flow field plate 1100 becomes an anode, and the oxidant flow field plate 1000 becomes a cathode with the result that an electric potential, *i.e.* voltage is developed between the fuel flow field plate 1000 and the oxidant flow field plate 1100. The above described electrochemical fuel cell is combined with others in a fuel cell stack to provide the desired level of electric power as described in the above-noted U.S. Patent 5,300,370.

The operation of Fuel Cell 500 requires that the electrodes 10 be porous to the fuel and oxidant fluids, e.g. hydrogen and oxygen, to permit these components to readily pass from the grooves 1400, 1200 through electrodes 10 to contact the catalyst 600 on the surfaces of the membrane 550, as shown in Figure 8(A), and enable protons derived from hydrogen to migrate through ion exchange membrane 550. In the electrode 10 of the present invention, channels 20 are positioned to adjacently cover grooves 1400, 1200 of the flow field plates so that the pressurized gas from the grooves passes through the smaller openings 60 of channels 20 and exits the larger openings 50 of channels 20. The initial velocity of the gas at the smaller openings 60 is higher than the gas flow at the larger openings 50 with the result that the gas is slowed down when it contacts the catalyst 600 on the surface of membrane 550 and the residence time of gas-catalyst contact is increased and the area of gas exposure at the membrane 550 is maximized. This feature, together with the increased electrical conductivity of the flexible graphite electrode of the present invention enables more efficient fuel cell operation. Alternatively, in certain circumstances it may be desirable to have the pressurized gas flow through the larger openings 50 of channels 20 and exit through the smaller openings 60 of channels 20.

In the present invention, for a flexible graphite sheet having a thickness of .003 inch to .015 inch adjacent the channels and a density of 0.5 to 1.5 g/cc, the preferred channel density (or count) is from 1000 to 3000 channels per square inch and the preferred channel size is a channel in which the ratio of the area of larger channel opening to the smaller is from 50:1 to 150:1.

As noted, flexible graphite sheet made in accordance with the present invention exhibits increased or enhanced isotropy when compared with flexible graphite sheet made using different sized (*i.e.*, larger) graphite flakes. This increased isotropy is useful in enhancing the sealing properties of gaskets made from the flexible graphite sheet, in providing decreased electrical resistivity across the plane of the sheet in electrolytic applications such as in fuel cell components, and in providing better thermal conductivity across the plane of the flexible graphite sheet.

The above description is intended to enable the person skilled in the art to practice the invention. It is not intended to detail all of the possible variations and modifications that will become apparent to the skilled worker upon reading the description. It is intended, however, that all such modifications and variations be included within the scope of the invention that is defined
5 by the following claims. The claims are intended to cover the indicated elements and steps in any arrangement or sequence that is effective to meet the objectives intended for the invention, unless the context specifically indicates the contrary.

What is claimed is:

1. A method for making flexible graphite sheet, the method comprising:
 - (i) providing graphite flake sized no more than about 30% by weight +80 mesh;
 - (ii) treating the graphite flake with an intercalating solution to obtain heat expandable, intercalated graphite flake;
 - (iii) exposing the intercalated graphite flake to an elevated temperature to exfoliate the intercalated graphite flake into expanded particles of graphite; and
 - (iv) passing the expanded particles of graphite through pressure rolls to form a compressed sheet having opposed major surfaces.
2. The method of claim 1 wherein the graphite flake is sized at least about 50% by weight 80 x 140 mesh.
3. The method of claim 2 wherein the graphite flake has a moisture content of no greater than about 1.0%.
4. The method of claim 3 which further comprises forming transverse fluid channels in the compressed sheet by mechanically impacting a surface of the sheet to displace graphite within the sheet at a plurality of predetermined locations.
5. The method of claim 4 which further comprises forming at least one groove in at least one of the surfaces of the sheet by mechanically impacting an opposed surface of the sheet.
6. A flexible graphite sheet comprising a compressed mass of expanded graphite particles, the expanded graphite particles formed from graphite flake sized no more than about 30% by weight +80 mesh prior to expansion.

7. The flexible graphite sheet of claim 6 wherein the graphite flake is sized at least about 50% by weight 80 x 140 mesh prior to expansion.

8. The flexible graphite sheet of claim 7 wherein the graphite flake has a moisture content of no greater than about 1.0% prior to expansion.

9. The flexible graphite sheet of claim 8 which further comprises a plurality of transverse fluid channels formed in the compressed sheet at a plurality of predetermined locations.

10. The flexible graphite sheet of claim 8 which further comprises at least one groove formed in at least one of the surfaces of the sheet by mechanically impacting an opposed surface of the sheet.

11. A membrane electrode assembly comprising a pair of electrodes and an ion exchange membrane positioned between the electrodes, at least one of the electrodes being formed of a sheet of a compressed mass of expanded graphite particles, the expanded graphite particles formed from graphite flake sized no more than about 30% by weight +80 mesh prior to expansion.

12. The assembly of claim 11 wherein the graphite flake is sized at least about 50% by weight 80 x 140 mesh prior to expansion.

13. The assembly of claim 12 wherein the graphite flake has a moisture content of no greater than about 1.0% prior to expansion.

14. The assembly of claim 11 which further comprises a plurality of transverse fluid channels formed in the compressed sheet at a plurality of predetermined locations.

15. The assembly of claim 11 which further comprises at least one groove formed in at least one of the surfaces of the sheet by mechanically impacting an opposed surface of the sheet.

16. A sealing gasket formed of a flexible roll-pressed sheet of expanded natural graphite the expanded graphite particles formed from graphite flake sized no more than about 30% by weight +80 mesh prior to expansion.

17. The gasket of claim 16 wherein the graphite flake is sized at least about 50% by weight 80 x 140 mesh prior to expansion.

18. The gasket of claim 17 wherein the graphite flake has a moisture content of no greater than about 1.0% prior to expansion.

19. The gasket of claim 16 which further comprises a plurality of transverse fluid channels formed in the compressed sheet at a plurality of predetermined locations.

20. The gasket of claim 16 which further comprises at least one groove formed in at least one of the surfaces of the sheet by mechanically impacting an opposed surface of the sheet.

FLEXIBLE GRAPHITE SHEET HAVING INCREASED ISOTROPY

Abstract of the Disclosure

The present invention relates to a flexible graphite sheet having increased isotropic properties. More particularly, the present invention relates to a flexible graphite sheet formed from particles of expanded natural graphite formed from graphite flake sized no more than about 30% by weight +80 mesh prior to expansion. The resulting sheet of flexible graphite exhibits improved conductive and fluid sealing properties.

X50 500μm 0000 Z1 36 SEI